


0301 KSS FLAME RETARDANT CABLE TIE



- Material: **UL94V-0** flame rated, UL approved Nylon 66.
- Color : White (standard), black color available.
- Feature : **94V-0** Flame Retardant.




| Item No. | Length | | W | Max. Bundle Dia. | Min. LoopTensile Strength | | Packing |
|-----------|--------|---------|-----|------------------|---------------------------|----|---------|
| | mm | inch | | | mm | mm | |
| CV-100V0 | 100 | 4" | 2.5 | 22 | 18 | 8 | 100pcs |
| CV-150V0 | 150 | 6" | 3.6 | 36 | 40 | 18 | |
| CV-200MV0 | 203 | 8" | 2.5 | 55 | 18 | 8 | |
| CV-200V0 | 203 | 8" | 4.6 | 52 | 50 | 22 | |
| CV-300SV0 | 300 | 11 7/8" | 4.8 | 83 | 50 | 22 | |
| CV-368V0 | 368 | 14 1/2" | 4.8 | 105 | 50 | 22 | |
| CV-380V0 | 380 | 15" | 7.6 | 105 | 120 | 55 | |

0301 KSS POLYPROPYLENE CABLE TIE



- Material: PP.
- Color: Black (natural color upon request)
- Feature: To use at chemical industry, provide better chemical resistant compare with standard cable tie.



| Item No. | Length | | W | Max. Bundle Dia. | Min. LoopTensile Strength | | Packing |
|-------------|--------|-----------|-----|------------------|---------------------------|----|---------|
| | mm | inch | | | mm | mm | |
| CV-150PPBK | 150 | 6" | 3.6 | 36 | 18 | 8 | 100pcs |
| CV-200PPBK | 200 | 8" | 4.6 | 52 | 22 | 10 | |
| CV-240LPPBK | 240 | 9 7/16" | 7.6 | 61 | 51 | 23 | |
| CV-250PPBK | 250 | 10" | 4.8 | 68 | 22 | 10 | |
| CV-300PPBK | 300 | 11 7/8" | 7.6 | 80 | 51 | 23 | |
| CV-380PPBK | 380 | 15" | 7.6 | 105 | 51 | 23 | |
| CV-550PPBK | 550 | 21 11/16" | 8.0 | 160 | 51 | 23 | |