


# 0225 KSS OC TYPE CABLE MARKER

- Material : **UL94V-0** flame rated, UL approved PVC.
  - Standard color: White body marker in black.
  - PVC service temperature: 85°C
  - Description:
    1. To be fitted after termination. The marker can be removed without breaking the terminal connection.
    2. O shape design benefit to grip the wire/cable tight.
    3. Clip on design enable it to grip wire/cable firmly in position after termination attached.
    4. Each marker will accommodate multiple wire sizes.
- ※OC-2L has wider entrance.



Item No.	Suitable Wire		Suitable Range mm	L mm	Std. Markings	Packing
	sq	AWG				
OC-1	0.5~0.75	20~18	2.5~3.0	4	Solid number or letter roll for 0~9, A~Z /, +, -, ÷, blank	1000pcs / Roll
OC-2	1.25~2.0	16~14	3.2~3.6			
※OC-2L	1.25~2.0	16~14	3.2~3.6			
OC-3	3.5~5.5	12~10	4.2~5.1			500pcs / Roll
OC-4	5.5~8.0	10~8	5.1~6.2			
OC-8	14	6	7.5~8.0	6.0	300pcs / Roll	

Wiring Ducts

Cable Markers

Cable Ties

Wrapping Bands

Cable Clamps &amp; Tie Mounts

Glands, Bushings

Conduits

Bushings

Wire Connectors

Tubes


Cable Clips

PCB Parts

Fasteners

# 0234 KSS MB TYPE CABLE MARKER

- Material : UL94HB flame rated Nylon 6.
- Color : Yellow, White
- Features :
  1. One size MB cable marker is suitable for different cable dia.
  2. Fast, snap-on installation.
  3. Flexible design, not easy to transfigure.
  4. High quality hot-foil stamped.
  5. Special inside stop point design makes MB marker keep in same direction, not overturn, marker read easily.



Item No.		Suitable Wire				Suitable Range I.D.	L	Std Markings	Packing
Yellow	White	sq	AWG	Fiber-optic	LAN cable	mm	mm		
MB-0	MB-0WE	0.75	18	2.0		2.2	4.0	Solid number or letter roll for 0~9, A~Z /, +, -, ÷, blank	100pcs
MB-1	MB-1WE	1.25~2.0	16-14	3.0		3.0~3.4			
MB-2	MB-2WE	3.5-5.5	12-10		CAT.5e	4.0~5.0			
MB-3	MB-3WE	8	8		CAT.6	5.2~6.0			
MB-4	MB-4WE				CAT.6	5.8~7.0			
MB-5	MB-5WE	14	6		CAT.6A	7.0~8.1	6.0		