

0616 KSS 快速型浪管固定头 EASY TYPE FLEXIBLE CONDUIT ADAPTOR

专利品



无卤素 环保

单位: mm



型 号 Item No.		螺纹外径 Thread O.D.	铁板孔径 Mounting Hole	适用浪管 Suitable Conduit	包装 Packing
灰色	黑色				
BGQ-16	BGQ-16BK	16.0	16.0+0.2	BG-16P	50pcs (附螺帽)
BGQ-18	BGQ-18BK	17.0	17.0+0.2	BG-18P	
BGQ-20	BGQ-20BK	20.0	20.0+0.2	BG-20P	
BGQ-22	BGQ-22BK	20.0	20.0+0.2	BG-22P	
BGQ-25	BGQ-25BK	25.0	25.0+0.3	BG-25P	
BGQ-26	BGQ-26BK	24.0	24.0+0.3	BG-26P	25pcs (附螺帽)
BGQ-32	BGQ-32BK	32.0	32.0+0.3	BG-32P	
BGQ-34	BGQ-34BK	32.5	32.5+0.3	BG-34P	

材质: UL合格之 NYLON 66 (黑色), 防火等级94V-2。

特点: 一体式设计, 安装简单迅速。

安 装 说 明



步骤1
将浪管推入固定头



步骤2
将迫紧环退出卡木



步骤3
旋转迫紧环即可固定浪管

0616 KSS 快速型浪管固定头 EASY TYPE FLEXIBLE CONDUIT ADAPTOR

专利品



无卤素 环保

单位: mm



PG规格 PG THREAD

型 号 Item No.	螺纹规格 Thread	螺纹外径 Thread O.D.	铁板孔径 Mounting Hole	适用浪管 Suitable Conduit	包装 Packing
PAQ-0707	PG7	15.2	12.5+0.2	PA-07	50pcs (附螺帽)
PAQ-0709	PG9	15.2	15.2+0.2	PA-07	
PAQ-1009	PG9	15.2	15.2+0.2	PA-10	
PAQ-1209	PG9	15.2	15.2+0.2	PA-12	
PAQ-1211	PG11	18.6	18.6+0.2	PA-12	
PAQ-12135	PG13.5	20.4	20.4+0.2	PA-12	
PAQ-1216	PG16	22.5	22.5+0.2	PA-12	
PAQ-17135	PG13.5	20.4	20.4+0.2	PA-17	
PAQ-1716	PG16	22.5	22.5+0.2	PA-17	25pcs (附螺帽)
PAQ-1721	PG21	28.3	28.3+0.3	PA-17	
PAQ-2321	PG21	28.3	28.3+0.3	PA-23	10pcs (附螺帽)
PAQ-2929	PG29	37.0	37.0+0.3	PA-29	
PAQ-3636	PG36	47.0	47.0+0.3	PA-36	10pcs (附螺帽)
PAQ-4848	PG48	59.3	59.3+0.3	PA-48	

材质: UL合格之 NYLON 66 (黑色), 防火等级94V-2。

特点: 一体式设计, 安装简单迅速。

安 装 说 明



步骤1
将浪管推入固定头



步骤2
将迫紧环退出卡木



步骤3
旋转迫紧环即可固定浪管

配线槽

配线标志

扎线带

结束带

固定座

固定头、浪管

保护部品

接线头

套管

固定夹

PC板部品

扣具