

# 0616 KSS EASY TYPE FLEXIBLE CONDUIT ADAPTOR



- Material: UL94V-2 flame rated, UL approved Nylon 66.
- Color: Black / Grey
- Feature : One piece design, easy and faster installation without tool.



Item No.		Mounting Hole	Suitable Conduit	Packing
Grey	Black			
BGQ-16	BGQ-16BK	16	BG-16P	50 pcs (with screw nut)
BGQ-18	BGQ-18BK	17	BG-18P	
BGQ-20	BGQ-20BK	20	BG-20P	
BGQ-22	BGQ-22BK	20	BG-22P	
BGQ-25	BGQ-25BK	25	BG-25P	
BGQ-26	BGQ-26BK	24	BG-26P	
BGQ-32	BGQ-32BK	32	BG-32P	25 pcs (with screw nut)
BGQ-34	BGQ-34BK	32.5	BG-34P	

## INSTALL INSTRUCTION



STEP1  
Insert the conduit into the adaptor.



STEP2  
Push lock out.



STEP3  
Turn it around for locking.

# 0616 KSS EASY TYPE FLEXIBLE CONDUIT ADAPTOR



- Material: UL94V-2 flame rated, UL approved Nylon 66.
- Color: Black
- Feature : One piece design, easy and faster installation without tool.



## PG THREAD

UNIT : mm

Item No.	Thread	Thread O.D.	Mounting Hole	Suitable Conduit	Packing
PAQ-0707	PG7	15.2	12.5+0.2	PA-07	50 pcs (with screw nut)
PAQ-0709	PG9	15.2	15.2+0.2	PA-07	
PAQ-1009	PG9	15.2	15.2+0.2	PA-10	
PAQ-1209	PG9	15.2	15.2+0.2	PA-12	
PAQ-1211	PG11	18.6	18.6+0.2	PA-12	
PAQ-12135	PG13.5	20.4	20.4+0.2	PA-12	
PAQ-1216	PG16	22.5	22.5+0.2	PA-12	
PAQ-17135	PG13.5	20.4	20.4+0.2	PA-17	
PAQ-1716	PG16	22.5	22.5+0.2	PA-17	
PAQ-1721	PG21	28.3	28.3+0.3	PA-17	
PAQ-2321	PG21	28.3	28.3+0.3	PA-23	25 pcs (with screw nut)
PAQ-2929	PG29	37.0	37.0+0.3	PA-29	
PAQ-3636	PG36	47.0	47.0+0.3	PA-36	10 pcs (with screw nut)
PAQ-4848	PG48	59.3	59.3+0.3	PA-48	

## INSTALL INSTRUCTION



STEP1  
Insert the conduit into the adaptor.



STEP2  
Push lock out.



STEP3  
Turn it around for locking.