

1215 KSS 黏貼式扭線環 MOUNTING TWIST TIE



無鹵素 環保


單位：mm



型號 Item No.	W	W1	H	束線範圍 Bundle Diameter	包裝 Packing
TTB-08	17.4	7.9	27.5	7~10	100pcs
TTB-15	22.0	14.8	35.2	10~15	
TTB-20	25.5	20.6	40.0	15~20	

材質：UL合格之NYLON 66 (本色)，防火等級94V-2，底座背膠。

- 特點：1.黏貼式設計，可省去面板鑽孔之麻煩。
- 2.束線簡易、牢固，並可鬆開，多次重複使用。



1216 KSS 黏貼式扣線套 ADHESIVE WIRE SADDLE




無鹵素 環保

單位：mm




型號 Item No.	L	W	W1	H2	包裝 Packing
AWS-11	19.8	20.0	11.2	11.0	100pcs
AWS-9R	16.0	29.8	8.5	13.6	
AWS-1210	18.3	20.7	11.3	10.0	
AWS-0912	9.5	15.8	9.0	11.6	


材質：UL合格之NYLON 66 (本色)，防火等級94V-2，底座背膠。




AWS-11



AWS-9R



AWS-1210



AWS-0912

1217 KSS 高壓隔離線圈 SPACERS RING




94V-0 無鹵素 環保

單位：mm




型號 Item No.	H1	H2	O.D.	包裝 Packing
SPR-8V0	14.2		28.0	100pcs
SPR-45V0	26.3	22	49.2	

材質：UL合格之 NYLON 66 (白色)，防火等級 94V-0。



SPR-8V0



SPR-45V0