


1215 KSS MOUNTING TWIST TIE



- Material: UL94V-2 flame rated, UL approved Nylon 66 with adhesive tape.
- Color: Natural.
- Peel off adhesive paper before usage, insert cables and twist on to fix.



UNIT : mm

Item No.	W	W1	H	Bundle Diameter	Packing
TTB-08	17.4	7.9	27.5	7~10	100pcs
TTB-15	22.0	14.8	35.2	10~15	
TTB-20	25.5	20.6	40.0	15~20	

1216 KSS ADHESIVE WIRE SADDLE




- Material: UL94V-2 flame rated, UL approved Nylon 66 with adhesive tape.
- Color: Natural.




UNIT : mm


Item No.	L	W	W1	H2	Packing
AWS-11	19.8	20.0	11.2	11.0	100pcs
AWS-9R	16.0	29.8	8.5	13.6	
AWS-1210	18.3	20.7	11.3	10.0	
AWS-0912	9.5	15.8	9.0	11.6	




AWS-11



AWS-9R



AWS-1210



AWS-0912

1217 KSS SPACERS RING




- Material: UL94V-0 flame rated, UL approved Nylon 66.
- Color: White.




UNIT : mm

Item No.	H1	H2	O.D.	Packing
SPR-8V0	14.2		28.0	100pcs
SPR-45V0	26.3	22	49.2	



SPR-8V0



SPR-45V0