





1401 KSS PLASTIC SCREWS



- Material: UL94HB flame rated, UL approved PC / UL94V-2 flame rated, UL approved Nylon 66.
- For better insulation, light weight, no rust.
- Used extensively as metal screw but where insulation is needed. Good for computer or electronics equipment fixation.
- For Nylon 66, Add "N" to Item No. UNIT : mm




	Item No.		Thread	W	H1	H2	Packing	
	PC	NYLON						
SCREW 		PF-205NK	M2x0.4	4.5	5.0	1.6	1000pcs	
		PF-208NK			8.0			
		PF-210NK			10.0			
		PF-306K	PF-306NK	M3x0.5	5.25	6.0		2.5
		PF-308K	PF-308NK			8.0		
		PF-310K	PF-310NK			10.0		
		PF-312K	PF-312NK			12.0		
		PF-408K	PF-408NK			8.0		
		PF-410K	PF-410NK	M4x0.7	7.5	10.0		2.6
		PF-412K	PF-412NK			12.0		
		PF-414K	PF-414NK			14.0		
		PF-420K	PF-420NK			20.0		
		PF-425K	PF-425NK			25.0		
		PF-520K	PF-520NK	M5x0.8	8.7	20.0		3.5
		PF-530K	PF-530NK			30.0		
		PF-540K	PF-540NK			40.0		
		PF-620K	PF-620NK	M6x1.0	10.0	20.0		4.0
		PF-630K	PF-630NK			30.0		
	PF-640K	PF-640NK	40.0					
NUT 	-	PN-2NK	M2x0.4	4.0	4.5	1.5		
		PN-3K	PN-3NK	M3x0.5	5.6	6.4	2.7	
		PN-4K	PN-4NK	M4x0.7	7.0	8.1	3.2	
		PN-5K	PN-5NK	M5x0.8	8.0	9.2	4.0	
		PN-6K	PN-6NK	M6x1.0	10.0	11.5	5.0	



- Material: UL94V-2 flame rated, UL approved Nylon 66.
- Color: Natural
- For better insulation, light weight, no rust.
- Used extensively as metal screw but where insulation is needed. Good for computer or electronics equipment fixation.



	Item No.	Thread	W	H1	H2	Packing
HEX HEAD SCREW 	PF-820N	M8x1.25	12.8	20	5.4	NYLON 100pcs
	PF-830N			30		
	PF-840N			40		
	PF-1030SN	M10x1.5	13.6	30	5.5	
	PF-1030N			30		
	PF-1040SN			40		
PF-1040N	40					
NUT 	PN-8N	M8x1.25	12.8	14.5	6.4	
	PN-10N	M10x1.5	16.7	19.2	8.0	

- Material: UL94V-2 flame rated, UL approved Nylon 66.



	Item No.	Thread	W	H1	H2	Packing
SCREW 	PF-823HN	Natural	M8x1.25	15.8	22.5	5.5
	PF-823HNGYJ	Grey				
NUT 	PN-8HN	Natural	M8x1.25	12.8	14.6	10
	PN-8HNGYJ	Grey				